



|                                   |                       |                                   |
|-----------------------------------|-----------------------|-----------------------------------|
| MODLE                             |                       | SELEXX/MATE                       |
| STROKE                            | X AXIS                | 1720 mm (5.643ft)                 |
|                                   | Y AXIS                | 2630 mm (8.628ft)                 |
|                                   | Z AXIS                | 250 mm (0.82ft)                   |
| TABLE SIZE                        |                       | 1300x2500mm (4.265x8.2ft)         |
| MAX.FEED SPEED                    | Y /X AXIS             | 80/50 M/min (262.45/164ft/min)    |
|                                   | Z AXIS                | 20 M/min (65.62ft/min)            |
| ATC HEAD WHIT                     | NO.1 OF SPINDLES      | 1                                 |
|                                   | TOOL HEADER SHANK     | HSK63F ,AIR COOLED                |
|                                   | NUMBER OF TOOLS       | 8                                 |
|                                   | ROTATION SPEED        | 1000~24000 RPM                    |
| BORING BLOCK                      | NO2. BLOCK(5x5)       | 4800RPM                           |
| TOOL DIA                          | FOR ROUTER BIT (O.D.) | MAX. 25mm (Φ0.984inch)            |
| SHANK                             | FOR BORING            | 10mm (Φ0.394inch)                 |
| POWER                             | ATC HEAD              | 7.5 Kw x1 (10HP)                  |
|                                   | VACUUM PUMP           | 5.5 Kw x2 (7.5HPX2)               |
|                                   | BORING                | 1.5Kw x1 (1HP)                    |
| AIR PRESSURE                      |                       | 6 KG/CM2 (85lb/in <sup>2</sup> )  |
| NC CONTROLLER                     |                       | ANDI-FANUC                        |
| DIMENSIONS                        | FLOOR AREA            | 10500x5000 mm (34.44x16.4ft)      |
|                                   | HIGHT                 | 2750 mm (9ft)                     |
|                                   | WEIGHT                | 58000 Kg (12786.8lb)              |
| SUCTION CAPACITY FOR MAIN SPINDLE |                       | 2695 M <sup>3</sup> /HR (9259cfm) |
| AIR CONSUMPTION                   |                       | 450 L/MIN (15.9cfm)               |
| TOTAL CONNECTED LOAD/RATED CURR   |                       | 35Kw/84/42/35A                    |
| SUCTION CONNECTION AT CUSTOMER    |                       | 1x 200 + 1xψ125                   |

