



MODLE		SELEXX/MATE
STROKE	X AXIS	1720 mm (5.643ft)
	Y AXIS	2630 mm (8.628ft)
	Z AXIS	250 mm (0.82ft)
TABLE SIZE		1300x2500mm (4.265x8.2ft)
MAX.FEED SPEED	Y /X AXIS	80/50 M/min (262.45/164ft/min)
	Z AXIS	20 M/min (65.62ft/min)
ATC HEAD WHIT	NO.1 OF SPINDLES	1
	TOOL HEADER SHANK	HSK63F ,AIR COOLED
	NUMBER OF TOOLS	8
	ROTATION SPEED	1000~24000 RPM
BORING BLOCK	NO2. BLOCK(5x5)	4800RPM
TOOL DIA	FOR ROUTER BIT (O.D.)	MAX. 25mm (Φ0.984inch)
SHANK	FOR BORING	10mm (Φ0.394inch)
POWER	ATC HEAD	7.5 Kw x1 (10HP)
	VACUUM PUMP	5.5 Kw x1 (7.5HP)
	BORING	1.5Kw x1 (2HP)
AIR PRESSURE		6 KG/CM2 (85lb/in ²)
NC CONTROLLER		ANDI-FANUC
DIMENSIONS	FLOOR AREA	5200x4000 mm (17.06x13.123ft)
	HIGHT	2300 mm (7.546ft)
	WEIGHT	3600 Kg (7929lb)
SUCTION CAPACITY FOR MAIN SPINDLE		2695 M ³ /HR (9259cfm)
AIR CONSUMPTION		450 L/MIN (15.9cfm)
TOTAL CONNECTED LOAD/RATED CURRENT		25Kw/45A
SUCTION CONNECTION AT CUSTOMER		1x 200

圖頁1